



| FOR OVER 20 YEARS



ABM[®] GLASS WOOL

Protect Your Project

FIREPROOF SOLUTION
INSULATION SOLUTION
SOUNDPROOF SOLUTION

ABM[®] GLASS WOOL

NORMAL SPECIFICATION

Density	10 ~ 96 kg/m ³
Thickness	25 ~ 200mm
Width	0,6 m / 1,22m
Length	1,2m ; 10m - 30m

* Above size are standard sizes, for other size please consult us



INTRODUCTION

ABM Glass Wool blankets are manufactured from fine and stable fibers bonded with thermosetting resins and formed into blankets, they are rot proof and free from shot due to its mineral composition.

ADVANTAGES



- Non combustible
- Easily installed
- Lightweight Insulation blanket
- Made from biosoluble formulation
- Reduces overall building energy usage
- Easily transported around site due to packaging
- Can easily be custom cut save installation time


APPLICATIONS

- Metallic Building
- Walling And Partitioning
- HVAC Duct Works
- Roof And Floor Application
- Suspended Ceiling




TECHNICAL PARAMETERS

PROPERTY	VALUE	STANDARD
Density	10 - 98 kg/m ³	ASTM C302 / C167
Thermal conductivity	0,034 – 0,062 (W/m.k)	ASTM C335
Surface burning characteristics	Class A	ASTM E84
Grade of combustibility	Non-combustible grade A (EURO CLASS A1)	EN 13162
Hydrophobicity	≥ 98	GB/T 10299
Moisture rate	≤ 5%	GB/T 5480.7
Water vapor sorption	< 5%	ASTM C1104
Linear shrinkage	3%	ASTM C356
Non-Fibrous(shot) content	≤ 3%	ASTM C1335
Sound absorption coefficient at 50mm (NRC)	0,9 - 1	ASTM C 423-01



1. Double Skin Roof System




2. Single Skin Roof System



GLASS WOOL ROLL FISHING

ABM Glass Wool roll can be faced with various Vapor Barrier, such as:

- FSK Aluminum Foil
- Double-sided Aluminum Foil
- White Polypropylene
- Perforated aluminum foil
- Kraft paper
- ...



**Other finishing material please contact us freely*



FOR OVER 20 YEARS

LICOM INSULATION CO.,LTD

60A Hoang Van Thu St, Ward 9, Phu Nhuan Dist,

Ho Chi Minh City, Vietnam.

Tell : (+84) 28 3997 6336

Ms.Tram Dang: 0909.433.711

Website: www.licom.com.vn